



#

ORGANIC S1 P

S1P ###, SR ###, ## ###, ## ###
#####. ### ###
#####.

##	###
##	##
###	SJ #
##	##
###	PU / PU
Top	##
####	S1 P / SRC
##	EU 35-42 / UK 3.0-8.0 / US 5.5-10.5 JPN 21.5-26.5 / KOR 230-270
##	0.476 kg
###	ASTM F2413:2018 EN ISO 20345:2011



S1P

#####



#####



#####



#####



#####



SRC

#####

##:
###, ##, ##, ##

##:

##:
#####. ### ##### ## ##### ## ##.

	##	## ##	##	EN ISO 20345
## ##	#### ##			
	##: ### ##	mg/cm²/h	6.9	≥ 0.8
	##: ### ##	mg/cm²	61.1	≥ 15
## ##	##			
	##: ### ##	mg/cm²/h	60.5	≥ 2
	##: ### ##	mg/cm²	484.1	≥ 20
###	SJ # ##			
	###: #####(##/##)(###)	##	25600/12800	25600/12800
###	PU / PU			
	### #####(## ##)	mm³	29.1	≤ 150
	### ## ## SRA: ###	##	0.40	≥ 0.28
	## SRA# ### ##: ##	##	0.39	≥ 0.32
	### ## ## SRB: ###	##	0.15	≥ 0.13
	## SRB# ### ##: ##	##	0.20	≥ 0.18
	### ## #	###	189.9	0.1 - 1000
	ESD #	###	N/A	0.1 - 100
	#### ## ##	J	27	≥ 20
Top	##			
	#### ## # (## # ##### 100J)	mm	N/A	N/A
	#### ## # (## # ## ## 10kN)	mm	N/A	N/A
	#### ## # (## # ## ## 200J)	mm	14.0	≥ 14
	#### ## # (## # ## ## 15kN)	mm	14.5	≥ 14

##:

##, ## ## ##### ## # #####. ## ##### ## Safety Jogger # ##### ##, ### ## ## ##### ## ##### ## ## # #####.



Solutions for every workplace

INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP

ENGINEERED
IN EUROPE

www.safetyjogger.com