

ORGANIC S1P LOW



```
## ##
## ## ## ##### ## ## ##
## ##### ##### ## ## ##
##### ## #####.
```

##:
####, ###, ##, ##, ##

##:
##, ## ##### ##, ## ##

##:
#####. ### ##### ## ##### ## ##.

	##	## ##	##	EN ISO 20345
## ##	#### ##, ### ##			
	##: ### ##	mg/cm²/h	3.3	≥ 0.8
	##: ### ##	mg/cm²	27.3	≥ 15
## ##	##			
	##: ### ##	mg/cm²/h	49.8	≥ 2
	##: ### ##	mg/cm²	398.8	≥ 20
###	SJ # ##			
	###: ####(##/##)(###)	##	Dry 25600 cycles/Wet 12800 cycles	25600/12800
###	PU / PU			
	### ####(## ##)	mm³	135.4	≤ 150
	## ## ## - ## + NaLS - ## ## ##	##	0.39	≥ 0.31
	## ## ## - ## + NaLS - ## ## ##	##	0.38	≥ 0.36
	SR ## ## - ## + #### - ##### ## ##	##	0.26	≥ 0.19
	SR ## ## - ## + #### - ## ## ##	##	0.29	≥ 0.22
	### ## #	###	200	0.1 - 1000
	ESD #	###	21.2	0.1 - 100
	#### ## ##	J	25	≥ 20
Top	##			
	#### ## # (## # ##### 100J)	mm	N/A	N/A
	#### ## # (## # ## ## 10kN)	mm	N/A	N/A
	#### ## # (## # ## ## 200J)	mm	15.5	≥ 14
	#### ## # (## # ## ## 15kN)	mm	19.5	≥ 14

##:

##, ## ## ##### ## # #####. ## ##### ## Safety Jogger # ##### ##, ### ## ## ## ## ##### ##### ## # #####.



Solutions for every workplace

INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP



www.safetyjogger.com