

**OXYCLOG** **OB**

##### SRA #####  
#####(135°C)#####  
#####(90°C)#####  
##### ESD #####.

|       |                                                      |
|-------|------------------------------------------------------|
| ## ## | TPE                                                  |
| ## ## | N/A                                                  |
| ###   | SJ # ##                                              |
| ###   | TPE                                                  |
| ####  | OB / ESD, A, SRA, E                                  |
| ## ## | EU 35-48 / UK 3.0- / US 5.5-<br>JPN 21.5- / KOR 230- |
| ## ## | 0.248 kg                                             |
| ###   | ASTM F2892:2018<br>EN ISO 20347:2012                 |



FUX



BLK



BLU



EBL



EGN



LBL



RED



WHT



##### ## ##  
##### ## # #####.



```
### ##
ESD# ## ### ##### # ## ###
##### ### ##### ##### ## ##
### #####. ## ### 100#####
100### #####.
```



**SRA**  
### ## ### ### # ##### ## ###  
## # #####. SRA ### ## ###  
### ## ##### ### ## ### #####  
#####.



90°C## ## ##  
90°C## ##### ## # #####.



### # ### ## ##  
# ### ### # ### ### #####.



```
#### ## ##
# ### ##, ## ### ## ##
### ### #####. ### ### ###
##### ## ## #####
##### ### #####.
```

## ##:  
##, ## # ##, ##  
  
## ##:  
### ##, ## ##### ##, ### ## ##, ## ##  
  
## ## ##:  
### ### ##### ##### ## ##### ## ##### ## #####. ### ##### ## ##### ## ##.

|       | ##                     | ## ##    | ##          | EN ISO 20347 |
|-------|------------------------|----------|-------------|--------------|
| ## ## | TPE                    |          |             |              |
|       | ##: ### ##             | mg/cm²/h | N/A         | ≥ 0.8        |
|       | ##: ### ##             | mg/cm²   | N/A         | ≥ 15         |
| ## ## | N/A                    |          |             |              |
|       | ##: ### ##             | mg/cm²/h | N/A         | ≥ 2          |
|       | ##: ### ##             | mg/cm²   | N/A         | ≥ 20         |
| ###   | SJ # ##                |          |             |              |
|       | ###: #####(##/##)(###) | ##       | 25600/12800 | 25600/12800  |
| ###   | TPE                    |          |             |              |
|       | ### #####(## ##)       | mm³      | 120         | ≤ 150        |
|       | ### ## ## SRA: ###     | ##       | 0.41        | ≥ 0.28       |
|       | ## SRA# ### ##: ##     | ##       | 0.41        | ≥ 0.32       |
|       | ### ## ## SRB: ###     | ##       | N/A         | ≥ 0.13       |
|       | ## SRB# ### ##: ##     | ##       | N/A         | ≥ 0.18       |
|       | ### ## #               | ###      | 90          | 0.1 - 1000   |
|       | ESD #                  | ###      | N/A         | 0.1 - 100    |
|       | #### ## #              | J        | 34          | ≥ 20         |

### ##:  
##### ## ##### ##, ## ## ##### ## # #####. ## ##### ## Safety Jogger # ##### ##, ### ## ## ##### ## ##### ##### ## # #####.



Solutions for every workplace

INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP

ENGINEERED  
IN EUROPE

www.safetyjogger.com