


**OXYCLOG** **OB**

SRA #####
#####(135°C)#####
#####(90°C)#####
ESD #####.


LBL




BLK



BLU



EBL



EGN



FUX



RED




WHT



#####



```
### ##
ESD# ## ### ##### # ## ###
##### ### ##### ##### ## ##
### #####. ## ### 100#####
100### #####.
```



SRA

#####. SRA ### ## ###

#####.



90°C## ## ##
90°C## ##### ## # #####.

#####.



```
#### ## ##
# ### ##, ## ### ## ##
### ### #####. ### ### ###
##### ## ## #####
##### #####.

```

##:
##, ## # ##, ##

##:
##, ## ##### ##, ### ## ##, ##

##:
##, ##### ##, ##### ##, ## ##.

	##	## ##	##	EN ISO 20347
## ##	TPE			
	##: ### ##	mg/cm²/h	N/A	≥ 0.8
	##: ### ##	mg/cm²	N/A	≥ 15
## ##	N/A			
	##: ### ##	mg/cm²/h	N/A	≥ 2
	##: ### ##	mg/cm²	N/A	≥ 20
###	SJ # ##			
	###: #####(##/##)(###)	##	25600/12800	25600/12800
###	TPE			
	### #####(## ##)	mm³	120	≤ 150
	### ## ## SRA: ###	##	0.41	≥ 0.28
	## SRA# ### ##: ##	##	0.41	≥ 0.32
	### ## ## SRB: ###	##	N/A	≥ 0.13
	## SRB# ### ##: ##	##	N/A	≥ 0.18
	### ## #	###	90	0.1 - 1000
	ESD #	###	N/A	0.1 - 100
	#### ## ##	J	34	≥ 20

##:
##, ## ## ##### ## # #####. ## ##### ## Safety Jogger # ##### ##, ### ## ## ##### ##, ##### ##, ##### # #####.