



# SAFETY JOGGER

PROFESSIONAL



Heavy

## OXYVA OB

## ### ####

### ### #### 30°C## ### # ### ESD ##, ## # ## ####  
 ### ### ####. ### # ## ### # ### # ####### ## # ####  
 #####.

|       |                                                                   |
|-------|-------------------------------------------------------------------|
| ## ## | ### EVA                                                           |
| ## ## | N/A                                                               |
| ###   | ### ##                                                            |
| ###   | ### EVA                                                           |
| ####  | OB / SR, ESD, A, E                                                |
| ## ## | EU 35-46 / UK 3.0-11.0 / US 3.0-12.0<br>JPN 21.5-30 / KOR 230-300 |
| ## ## | 0.220 kg                                                          |
| ###   | ASTM F2892:2018<br>EN ISO 20347:2022(Europe)                      |



BLK



EBL



EGN



FUX



LIC



NAV



WHT



#### ## ###  
 # ### ##, ## ### ## ## ##  
 ### ### #######. ### ### ##  
 ##### # ## ### ##  
 ##### ## ## ##.



#### ##  
 ESD# ## ### ## ## ##  
 ##### ## ## ## ##  
 #####. ## ### 100#####  
 100### #####.



30°C## ## ##  
 # ### 30°C# #### ## # ##.



#### ## ## ##  
 # ### ## # ## ## ##.

SAFETY JOGGER  
WORKS

Solutions for every workplace

INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP

ENGINEERED  
IN EUROPE

www.safetyjogger.com

## ##:  
##, ####, ##, ## # ##

## ##:  
### ##, ## ##

## ## ##:  
### ## ##### ##### ## ##### ## ##### ## #####. ### ##### ## ##### ## ##.

|       | ##                               | ## ##    | ##          | EN ISO 20347 |
|-------|----------------------------------|----------|-------------|--------------|
| ## ## | ### EVA                          |          |             |              |
|       | ##: ### ##                       | mg/cm²/h | N/A         | ≥ 0.8        |
|       | ##: ### ##                       | mg/cm²   | N/A         | ≥ 15         |
| ## ## | N/A                              |          |             |              |
|       | ##: ### ##                       | mg/cm²/h | N/A         | ≥ 2          |
|       | ##: ### ##                       | mg/cm²   | N/A         | ≥ 20         |
| ###   | ### ##                           |          |             |              |
|       | ###: ####(##/##)(###)            | ##       | 25600/12800 | 25600/12800  |
| ###   | ### EVA                          |          |             |              |
|       | ### ####(## ##)                  | mm³      | 130         | ≤ 150        |
|       | ## ## ## - ## + NaLS - ## ## ##  | ##       | 0.31        | ≥ 0.31       |
|       | ## ## ## - ## + NaLS - ## ## ##  | ##       | 0.36        | ≥ 0.36       |
|       | SR ## ## - ## + ## - ##### ## ## | ##       | 0.19        | ≥ 0.19       |
|       | SR ## ## - ## + ## - ## ## ##    | ##       | 0.22        | ≥ 0.22       |
|       | ### ## #                         | ###      | 29.4        | 0.1 - 1000   |
|       | ESD #                            | ###      | 6.8         | 0.1 - 100    |
|       | #### ## ##                       | J        | 77          | ≥ 20         |

### ##:  
##### ## ##### ##, ## ## ##### ## # #####. ## ##### ## Safety Jogger # ##### ##, ### ## ## #### ## ##### ##### ## # #####.