



Heavy

OXYVA OB

###

30°C## ## # ## ESD ##, ## # ## ##
#####. ### ## ## ## # ## ## ##### ## ## ##
#####.

## ##	### EVA
## ##	N/A
###	### ##
###	### EVA
####	OB / SR, ESD, A, E
## ##	EU 35-46 / UK 3.0-11.0 / US 3.0-12.0 JPN 21.5-30 / KOR 230-300
## ##	0.220 kg
###	ASTM F2892:2018 EN ISO 20347:2022(Europe)



LIC



EBL



BLK



EGN



FUX



NAV



WHT




```
#####
#   ##, ##   ##   ##
###   #####.   ##
####   ##   ##   ##
####   ##   ##.
```



```
### ##
ESD# ## ### ##### # ## ###
##### ### ##### ##### ## ##
### #####. ## ### 100#####
100### #####.
```



30°C## ## ##
30°C# ##### ## # #####.



#####.

##:
##, ####, ##, ## # ##

##:
##, ##

##:
#####. ### ##### ## ##### ## ##.

	##	## ##	##	EN ISO 20347
## ##	### EVA			
	##: ### ##	mg/cm²/h	N/A	≥ 0.8
	##: ### ##	mg/cm²	N/A	≥ 15
## ##	N/A			
	##: ### ##	mg/cm²/h	N/A	≥ 2
	##: ### ##	mg/cm²	N/A	≥ 20
###	### ##			
	###: ####(##/##)(###)	##	25600/12800	25600/12800
###	### EVA			
	### ####(## ##)	mm³	130	≤ 150
	## ## ## - ## + NaLS - ## ## ##	##	0.31	≥ 0.31
	## ## ## - ## + NaLS - ## ## ##	##	0.36	≥ 0.36
	SR ## ## - ## + ## - ##### ## ##	##	0.19	≥ 0.19
	SR ## ## - ## + ## - ## ## ##	##	0.22	≥ 0.22
	### ## #	###	29.4	0.1 - 1000
	ESD #	###	6.8	0.1 - 100
	#### ## ##	J	77	≥ 20

##:
##, ## ## ##### ## # #####. ## ##### ## Safety Jogger # ##### ##, ### ## ## ## ## ##### ##### ## # #####.



Solutions for every workplace

INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP

ENGINEERED
IN EUROPE

www.safetyjogger.com