



**SAFETY
JOGGER**
PROFESSIONAL



Heavy

OXYVA OB

##

30°C## ## ## ## ESD ##, ## ## ## ## ##

#####.

## ##	### EVA
## ##	N/A
###	### ##
###	### EVA
####	OB / SR, ESD, A, E
## ##	EU 35-46 / UK 3.0-11.0 / US 3.0-12.0 JPN 21.5-30 / KOR 230-300
## ##	0.220 kg
###	ASTM F2892:2018 EN ISO 20347:2022(Europe)



WHT



EBL



BLK



EGN



FUX



LIC



NAV



##, ## ## ## ## ##

#####.



ESD# ##
#####. ## ## ## 100#####
100### ## ## ##.



30°C## ## ##
30°C# ## ## ## ## ##.



##.

**SAFETY
JOGGER**
WORKS

Solutions for every workplace

INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP

ENGINEERED
IN EUROPE

www.safetyjogger.com

##:
##, ####, ##, ## # ##

##:
##, ##

##:
#####. ### ##### ## ##### ## ##.

	##	## ##	##	EN ISO 20347
## ##	### EVA			
	##: ### ##	mg/cm²/h	N/A	≥ 0.8
	##: ### ##	mg/cm²	N/A	≥ 15
## ##	N/A			
	##: ### ##	mg/cm²/h	N/A	≥ 2
	##: ### ##	mg/cm²	N/A	≥ 20
###	### ##			
	###: ####(##/##)(###)	##	25600/12800	25600/12800
###	### EVA			
	### ####(## ##)	mm³	130	≤ 150
	## ## ## - ## + NaLS - ## ## ##	##	0.31	≥ 0.31
	## ## ## - ## + NaLS - ## ## ##	##	0.36	≥ 0.36
	SR ## ## - ## + ## - ##### ## ##	##	0.19	≥ 0.19
	SR ## ## - ## + ## - ## ## ##	##	0.22	≥ 0.22
	### ## #	###	29.4	0.1 - 1000
	ESD #	###	6.8	0.1 - 100
	#### ## ##	J	77	≥ 20

##:
##, ## ## ##### ## # #####. ## ##### ## Safety Jogger # ##### ##, ### ## ## ## ## ##### ##### ## # #####.



Solutions for every workplace

INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP

ENGINEERED
IN EUROPE

www.safetyjogger.com