

PACCOS1LOW

##

```
#### ## #####. PACCO S1P# ## ## ## ## ## ## ## ##
## ## #####. ## ## ## ## ##### ## ## #####. ## ## ##
## #####.
```


## ##	## ##
## ##	##
###	SJ ### # ###
##	## ## ##
###	###/##
Top	##
####	S1 PS / SR, ESD
## ##	EU 35-48 / UK 3.0-13.0 / US 3.0-13.5 JPN 21.5-31.5 / KOR 230-315
## ##	0.470 kg
###	ASTM F2413:2018 EN ISO 20345:2022



WHT



BLK



```
## ##
### ## ##### ## #####
#####. ## ## ##### ## ## #
##### ## ##### ## #####.
```




S1P

##, ## ##, ### # ##
#####? #### S1P ####
#####.



```
## ## ##
### ## ## ##### ## ## ##.
### ## ## 100% ## ## #####
#####.
```



```
###
## ### ### #####, ### # ##, ##
##### ## ##, ##, ## # ### ##
### ## ## # ### ## #### ## ##
### #####.
```



#####.



```
### ##
ESD# ## ### ##### # ## ###
##### ### ##### ##### ## ##
### #####. ## ### 100#####
100### #####.
```

##:
####, ###, ##, ##

##:
##, ## #####

##:
#####. ### ##### ## ##### ### #####.

	##	## ##	##	EN ISO 20345
## ##	## ##			
	##: ### ##	mg/cm²/h	1.20	≥ 0.8
	##: ### ##	mg/cm²	18.50	≥ 15
## ##	##			
	##: ### ##	mg/cm²/h	34.59	≥ 2
	##: ### ##	mg/cm²	277	≥ 20
###	SJ ### # ###			
	###: ####(##/##)(###)	##	Dry 25600 cycles/Wet 12800 cycles	25600/12800
###	###/##			
	### ####(## ##)	mm³	129mm³(Density:1.16)	≤ 150
	## ### ## - ### + NaLS - ## ### #####	##	0.36	≥ 0.31
	## ### ## - ### + NaLS - ## ## ###	##	0.44	≥ 0.36
	SR ### ## - ### + ##### - ##### ### ##	##	0.25	≥ 0.19
	SR ### ## - ### + ##### - ## ## ###	##	0.31	≥ 0.22
	### ## #	###	53.1	0.1 - 1000
	ESD #	###	11	0.1 - 100
	#### ### ##	J	25	≥ 20
Top	##			
	#### ## # (## # ##### 100J)	mm	NA	N/A
	#### ## # (## # ## ## 10kN)	mm	NA	N/A
	#### ## # (## # ## ## 200J)	mm	15	≥ 14
	#### ## # (## # ## ## 15kN)	mm	17	≥ 14

##:

###, ## ## ##### ### # #####. ## ##### ### Safety Jogger # ##### ###, ### ## ## ### ## ##### ##### ### # #####.



Solutions for every workplace

INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP

ENGINEERED
IN EUROPE

www.safetyjogger.com