

Light

ROCKET81 S1 P

Low-cut safety shoe with zone traction and tripguard

Safety Jogger's ROCKET81 low-cut safety shoes are your perfect safety solution in dry environments. Featuring S1P and SR slip resistance, they offer secure footing, antistatic properties, and comfort all day. Ideal for various industries, these shoes are metal-free, resist hot surfaces, and offer protection from falling objects.

Upper	Nubuck Action Leather
Lining	Mesh
Footbed	SJ foam footbed
Midsole	Anti-puncture Textile
Toecap	Composite
Category	S1 P / SRC, HRO
Size range	EU 37-48 / UK 4.0-13.0 / US 4.5-13.5 JPN 23-31.5 / KOR 240-315
Sample weight	0.590 kg
Norms	ASTM F2413:2018 EN ISO 20345:2011



BLK




Shoes For Crews

Shoes For Crews safety and occupational footwear provides enhanced traction, slip resistance when walking on different slippery surfaces and much more.



S1P

You work in dry environments, no risk of water/liquid sprays, and you need protection for your toes, protection against perforation, and a good breathability? Then you need S1P safety footwear.




Metal free

Metal free safety shoes are in general lighter than regular safety shoes. They are also very beneficial for professionals who have to pass through metal detectors several times a day.



SRC slip resistance

Slip resistant soles are one of the most important features of safety and occupational footwear. SRC slip resistant soles pass both SRA and SRB slip resistant tests, they are tested on both steel and ceramic surfaces.



Antistatic

Antistatic footwear prevents build-up of static electrical charges and ensures that they are discharged effectively. Volume resistance between 100 KiloOhm and 1 GigaOhm

Industries:

Automotive, Catering, Cleaning, Food & beverages, Industry

Environments:

Dry environment

Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20345
Upper	Nubuck Action Leather			
	Upper: permeability to water vapor	mg/cm²/h	3.6	≥ 0.8
	Upper: water vapor coefficient	mg/cm²	33.2	≥ 15
Lining	Mesh			
	Lining: permeability to water vapor	mg/cm²/h	60.1	≥ 2
	Lining: water vapor coefficient	mg/cm²	481.1	≥ 20
Footbed	SJ foam footbed			
	Footbed: abrasion resistance (dry/wet) (cycles)	cycles	25600/12800	25600/12800
Toecap	Composite			
	Impact resistance toecap (clearance after impact 100J)	mm	N/A	N/A
	Compression resistance toecap (clearance after compression 10kN)	mm	N/A	N/A
	Impact resistance toecap (clearance after impact 200J)	mm	18.5	≥ 14
	Compression resistance toecap (clearance after compression 15kN)	mm	21.5	≥ 14

Sample size: 42

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.



Solutions for every workplace

INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP



www.safetyjogger.com