

Medium

SAFETYRUN S1 P

#####

#####. ### ## ### ## ##,
#####.

## ##	## ##### ##
## ##	##
###	SJ Eco
##	##
###	PU
Top	##
####	S1 P / SR, FO
## ##	EU 35-48 / UK 3.0-13.0 / US 3.0-13.5 JPN 21.5-31.5 / KOR 230-315
## ##	0.590 kg
###	ASTM F2413:2018 EN ISO 20345:2022



BLK



S1P

```
### ## ## ## ## ##
#### ##, ## ##, ## # ##
### #####? #### S1P ####
#####.
```

**SRC**

```
### ## ## ## # ##### ## ##
## # #####. SRC ## ## ##
### ## ## ##### SRA #
SRB ### ##### ## #####.
```




##

```
##### ### ##### ##### ## #####  
### ## ####.
```



###

```
## ## ## ##### ##### ## ## ##
## ##### ##### ##### ## ## ##
##### ## #####.
```



#####

####.



##

```
### ## ### ##### ### ##### #####
### #####. 100##### 1### ###
## ##
```

##:
###, ##, ##, ##, ###, ## # ##, ##

##:
##

##:
#####. ### ##### ## ##### ## ##.

	##	## ##	##	EN ISO 20345
## ##	## ##### ##			
	##: ### ##	mg/cm²/h	2.2	≥ 0.8
	##: ### ##	mg/cm²	25	≥ 15
## ##	##			
	##: ### ##	mg/cm²/h	657.7	≥ 2
	##: ### ##	mg/cm²	525.8	≥ 20
###	SJ Eco			
	###: ####(##/##)(###)	##	25600/12800	25600/12800
###	PU			
	### #####(## ##)	mm³	55	≤ 150
	## ## ## - ## + NaLS - ## ## ##	##	0.40	≥ 0.31
	## ## ## - ## + NaLS - ## ## ##	##	0.39	≥ 0.36
	SR ## ## - ## + ##### - ##### ## ##	##	0.28	≥ 0.19
	SR ## ## - ## + ##### - ## ## ##	##	0.26	≥ 0.22
	### ## #	###	270	0.1 - 1000
	ESD #	###	N/A	0.1 - 100
	#### ## ##	J	26	≥ 20
Top	##			
	#### ## #(## # ##### 100J)	mm	N/A	N/A
	#### ## #(## # ## ## 10kN)	mm	N/A	N/A
	#### ## #(## # ## ## 200J)	mm	16	≥ 14
	#### ## #(## # ## ## 15kN)	mm	17	≥ 14

##:
##, ## ## ##### ## # #####. ## ##### ## Safety Jogger # ##### ##, ### ## ## ## ## ##### ##### ## # #####.