

Medium

SAFETYBOY WINTER S1P

SFTYBOYWNT

###.###.###.###.###.###.###.###.

```
##### S1# #####, ## ##, ## ##, ## ##,
##### ## ## ## ## ## ## ## ## ##. ## ## ## ##
#####.
```

## ##	## ##### ##
## ##	##
###	##
##	##
###	PU
Top	##
####	S1 P / SRC, CI
## ##	EU 35-48 / UK 3.0-13.0 / US 3.0-13.5 JPN 21.5-31.5 / KOR 230-315
## ##	0.620 kg
###	ASTM F2413:2018 EN ISO 20345:2011



BLK



#####.



```
### ##
### ## ### ##### ### ##### #####
### #####. 100##### 1### ###
## ##
```



```
#### ##
#### #### #### #### #### ## # ####
##### #### #####.
```



#####.



```
### ##
### ##### ##### ## ##### ###
##### ## #####.
```

##:
####, ##, ##, ## # ##, ##

##:
##, ## ##### ##, ### ##, ### ##

##:
#####. ### ##### ## ##### ## ##.

	##	## ##	##	EN ISO 20345
## ##	## ##### ##			
	##: ### ##	mg/cm²/h	1.18	≥ 0.8
	##: ### ##	mg/cm²	15	≥ 15
## ##	##			
	##: ### ##	mg/cm²/h	83.25	≥ 2
	##: ### ##	mg/cm²	666	≥ 20
###	##			
	###: ####(##/##)(###)	##	25600/12800	25600/12800
###	PU			
	### #####(## ##)	mm³	78	≤ 150
	### ## ## SRA: ###	##	0.35	≥ 0.28
	## SRA# ### ##: ##	##	0.33	≥ 0.32
	### ## ## SRB: ###	##	0.14	≥ 0.13
	## SRB# ### ##: ##	##	0.19	≥ 0.18
	### ## #	###	46.8	0.1 - 1000
	ESD #	###	N/A	0.1 - 100
	#### ## ##	J	33	≥ 20
Top	##			
	#### ## # (## # ##### 100J)	mm	N/A	N/A
	#### ## # (## # ## ## 10kN)	mm	N/A	N/A
	#### ## # (## # ## ## 200J)	mm	18.0	≥ 14
	#### ## # (## # ## ## 15kN)	mm	19.5	≥ 14

##:

###, ## ## ##### ## # #####. ## ##### ### Safety Jogger # ##### ###, ### ## ## ### ## ##### ##### ## # #####.



Solutions for every workplace

INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP

ENGINEERED
IN EUROPE

www.safetyjogger.com