



SAFETY JOGGER

PROFESSIONAL



Heavy

SONIC OB

###

####. #### #### ## ####
####. ## # ## #### ####.

## ##	### EVA
## ##	N/A
###	N/A
###	### EVA
####	OB / SR, ESD, A, E
## ##	EU 35-46 / UK 3.0-11.0 / US 3.0-12.0 JPN 21.5-30 / KOR 230-300
## ##	0.177 kg
###	ASTM F2892:2018 EN ISO 20347:2022(Europe)



BLK



EGN



EBL



FUX



LIC



NAV



WHT



##, ## #### ## ##
####. ### #### ##

####.



ESD# ## #### ## ##

####. ## ## 100####
100### ####.



30°C## ## ##
30°C# #### ## # ####.



####.

SAFETY JOGGER
WORKS

Solutions for every workplace

INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP

ENGINEERED
IN EUROPE

www.safetyjogger.com

##:

##, ##

##:

##, ### ## ##, ##

##:

#####. ### ##### ## ##### ### ##.

##	## ##	##	EN ISO 20347
## ##	### EVA		
	##: ### ##	mg/cm²/h	N/A ≥ 0.8
	##: ### ##	mg/cm²	N/A ≥ 15
## ##	N/A		
	##: ### ##	mg/cm²/h	N/A ≥ 2
	##: ### ##	mg/cm²	N/A ≥ 20
###	N/A		
	###: ####(##/##)(###)	##	N/A 25600/12800
###	### EVA		
	### ####(## ##)	mm³	108.8 ≤ 150
	## ## ## - ## + NaLS - ## ## ##	##	0.38 ≥ 0.31
	## ## ## - ## + NaLS - ## ## ##	##	0.37 ≥ 0.36
	SR ## ## - ## + ## - ##### ## ##	##	0.27 ≥ 0.19
	SR ## ## - ## + ## - ## ## ##	##	0.23 ≥ 0.22
	### ## #	###	2.0 0.1 - 1000
	ESD #	###	6.6 0.1 - 100
	#### ## ##	J	43 ≥ 20

##:

##, ## ## ##### ## # #####. ## ##### ## Safety Jogger # ##### ##, ### ## ## ## ## ##### ##### ## # #####.