



Medium

TACTIC OB

#####. 562g# ### ## #####.

## ##	## ## ##, ##
## ##	##
###	SJ # ##
###	##
####	OB / SR, LG, E, ##, CI, FO, HRO
## ##	EU 35-48 / UK 3.0-13.0 / US 3.0-13.5 JPN 21.5-31.5 / KOR 230-315
## ##	0.705 kg
###	EN ISO 20347:2022+A1:2024 ASTM F2892:2024



BLK



SRA

#####. SRA ### ## ##

####.



300°C# ### ## # #####.



##.



#####.

##:

##, ###

##:

##, ### ##

##:

#####. ### ##### ## ##### ## #####.

##	## ##	##	EN ISO 20347
## ##	## ## ##, ##		
	##: ### ##	mg/cm²/h	4.5 ≥ 0.8
	##: ### ##	mg/cm²	35 ≥ 15
## ##	##		
	##: ### ##	mg/cm²/h	45 ≥ 2
	##: ### ##	mg/cm²	350 ≥ 20
###	SJ # ##		
	###: ####(##/##)(###)	##	25600/12800 25600/12800
###	##		
	### #####(## ##)	mm³	85 ≤ 150
	## ## ## - ## + NaLS - ## ## ##	##	0.33 ≥ 0.31
	## ## ## - ## + NaLS - ## ## ##	##	0.37 ≥ 0.36
	SR ## ## - ## + ## - ##### ## ##	##	N/A ≥ 0.19
	SR ## ## - ## + ## - ## ## ##	##	N/A ≥ 0.22
	### ## #	###	N/A 0.1 - 1000
	ESD #	###	N/A 0.1 - 100
	#### ## ##	J	N/A ≥ 20

##:

##, ## ## ##### ## # #####. ## ##### ## Safety Jogger # ##### ##, ### ## ## ##### ## ##### ##### ## # #####.