



Medium

TACTIC LOW OB

TACTICLOW

allround tactical low-cut shoe

## ##	## ## ##, ##
## ##	##
###	SJ # ##
###	##
####	OB / SR, LG, E, ##, CI, FO, HRO
## ##	EU 35-48
## ##	0.600 kg
###	EN ISO 20347:2022+A1:2024
###	ASTM F3445:2024



BLK



SRA


#####. SRA ## ## ## ##

####.



##

300°C# ## ## # ####.



#####

##.



##

##.



Solutions for every workplace

INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP

ENGINEERED
IN EUROPE

www.safetyjogger.com

##:

##, ###

##:

##, ###

##:

#####. ### ##### ## ##### ## ##.

##	## ##	##	EN ISO 20347
## ##	## ## ##, ##		
	##: ### ##	mg/cm²/h	4.5 ≥ 0.8
	##: ### ##	mg/cm²	35 ≥ 15
## ##	##		
	##: ### ##	mg/cm²/h	45 ≥ 2
	##: ### ##	mg/cm²	350 ≥ 20
###	SJ # ##		
	###: ####(##/##)(###)	##	25600/12800 25600/12800
###	##		
	### #####(## ##)	mm³	85 ≤ 150
	## ## ## - ## + NaLS - ## ## ##	##	0.33 ≥ 0.31
	## ## ## - ## + NaLS - ## ## ##	##	0.37 ≥ 0.36
	SR ## ## - ## + ## - ##### ## ##	##	N/A ≥ 0.19
	SR ## ## - ## + ## - ## ## ##	##	N/A ≥ 0.22
	### ## #	###	N/A 0.1 - 1000
	ESD #	###	N/A 0.1 - 100
	#### ## ##	J	38 ≥ 20

##:

##, ## ## ##### ## # #####. ## ##### ## Safety Jogger # ##### ##, ### ## ## ## ## ##### ##### ## # #####.