



##


#####

## ##	## ##
## ##	####
###	SJ # ##
##	## ## ##
###	###/##
Top	##
#####	S7S / SR, CI, FO, HRO
## ##	EU 36-48 / UK 3.5-13.0 / US 4.0-13.5 JPN 22.5-31.5 / KOR 235-315
## ##	0.780 kg
###	EN ISO 20345:2022+A1:2024 ASTM F2413:2024



S3
S3 #####
#####. # ##

#####.



SRC


#####. SRC ### ## ###
SRA #
SRB ### ##### ## #####.



```
##
## ### ### ## ### ##### ##
#####.
```



300°C# ### ## # ####.



```
###
### ## ##### ##### ## #####
#####. ## ## ##### ## ## #
##### ## ##### ## #####.
```



```
## ##
#### ## ##### # ## ## ##### #####.
```

##:
##, ##, ###, ## # ##, ##, ###

##:
##, ### ## ##, ## ##

##:
#####. ### ##### ## ##### ## ##.

	##	## ##	##	EN ISO 20345
## ##	## ##			
	##: ### ##	mg/cm²/h	4.12	≥ 0.8
	##: ### ##	mg/cm²	41	≥ 15
## ##	####			
	##: ### ##	mg/cm²/h	3.36	≥ 2
	##: ### ##	mg/cm²	27	≥ 20
###	SJ # ##			
	###: ####(##/##)(###)	##	25600/12800	25600/12800
###	###/##			
	### #####(## ##)	mm³	83	≤ 150
	## ## ## - ## + NaLS - ## ## ##	##	0.39	≥ 0.31
	## ## ## - ## + NaLS - ## ## ##	##	0.46	≥ 0.36
	SR ## ## - ## + ##### - ##### ## ##	##	0.24	≥ 0.19
	SR ## ## - ## + ##### - ## ## ##	##	0.25	≥ 0.22
	### ## #	###	16.8	0.1 - 1000
	ESD #	###	N/A	0.1 - 100
	#### ## ##	J	29	≥ 20
Top	##			
	#### ## # (## # ##### 100J)	mm	N/A	N/A
	#### ## # (## # ## ## 10kN)	mm	N/A	N/A
	#### ## # (## # ## ## 200J)	mm	19.5	≥ 14
	#### ## # (## # ## ## 15kN)	mm	22.5	≥ 14

##:
##, ## ## ##### ## # #####. ## ##### ## Safety Jogger # ##### ##, ### ## ## ## ## ##### ##### ## # #####.



Solutions for every workplace
INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP



www.safetyjogger.com