

Medium

X0500 S2

##

Safety Jogger X0500# ## ## ## ## ## ## ## ## ##
#####. ## # ##, ## ## ##, ## ## ## ## ## ##
#####.

##

#####

SJ #

N/A

PU / PU

Top ##

S2 / SRC

EU 35-48 / UK 3.0-13.0 / US 3.0-13.5

JPN 21.5-31.5 / KOR 230-315

0.525 kg

ASTM F2413:2018

EN ISO 20345:2011



##

#####.




SRC

#####. SRC ## ## ##
SRA #
SRB ## ## ## ## ##.



##(WRU)

#####.



#####

##.



##

#####.



HACCP

HACCP# ## ## ## ## ##

#####. ## ## ## ##
HACCP ## ## ## ## ##
#####.

##:
####, ##, ##, ## # ##, ##, ##

##:
##, ### ## ##, ## ##

##:
#####. ### ##### ## ##### ## ##.

	##	## ##	##	EN ISO 20345
## ##	## ## ##			
	##: ### ##	mg/cm²/h	2.03	≥ 0.8
	##: ### ##	mg/cm²	21	≥ 15
## ##	####			
	##: ### ##	mg/cm²/h	18.27	≥ 2
	##: ### ##	mg/cm²	147	≥ 20
###	SJ # ##			
	###: #####(##/##)(###)	##	25600/12800	25600/12800
###	PU / PU			
	### #####(## ##)	mm³	46	≤ 150
	### ## ## SRA: ###	##	0.35	≥ 0.28
	## SRA# ### ##: ##	##	0.35	≥ 0.32
	### ## ## SRB: ###	##	0.14	≥ 0.13
	## SRB# ### ##: ##	##	0.18	≥ 0.18
	### ## #	###	66.7	0.1 - 1000
	ESD #	###	N/A	0.1 - 100
	#### ## ##	J	29	≥ 20
Top	##			
	#### ## # (## # ##### 100J)	mm	N/A	N/A
	#### ## # (## # ## ## 10kN)	mm	N/A	N/A
	#### ## # (## # ## ## 200J)	mm	16	≥ 14
	#### ## # (## # ## ## 15kN)	mm	18	≥ 14

##:

##, ## ## ##### ## # #####. ## ##### ## Safety Jogger # ##### ##, ### ## ## ##### ## ##### ##### ## # #####.