



SAFETY JOGGER

INDUSTRIAL



Medium

X1110 S3S

#####

X1110 #####. ##, ## ## ## ##, ## ## ## ## ##.

##	##
##	###
###	SJ #
##	##
###	PU / PU
Top	##
####	S3S / SR, CI, FO
##	EU 35-47 / UK 3.0-12.0 / US 3.0-13.0
	JPN 21.5-31 / KOR 230-310
##	0.653 kg
###	ASTM F2413:2018
	EN ISO 20345:2022+A1:2024



S3
S3 #####
#####. #
#####




#####.




SJ

#####. #
100%#



#####. #
#####



#####.



SRA

#####. SRA #

#####.

SAFETY
JOGGER
WORKS

Solutions for every workplace

INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP

ENGINEERED
IN EUROPE

www.safetyjogger.com

##:
###, ##, ##, ##, ###, ## # ##, ##, ###

##:
##, ### ##, ### ## ##, ##

##:
#####. ### ##### ## ##### ## ##.

	##	## ##	##	EN ISO 20345
## ##	## ## ##			
	##: ### ##	mg/cm²/h	2.86	≥ 0.8
	##: ### ##	mg/cm²	30	≥ 15
## ##	####			
	##: ### ##	mg/cm²/h	26.68	≥ 2
	##: ### ##	mg/cm²	214	≥ 20
###	SJ # ##			
	###: ####(##/##)(###)	##	25600/12800	25600/12800
###	PU / PU			
	### #####(## ##)	mm³	33	≤ 150
	## ## ## - ## + NaLS - ## ## ##	##	0.39	≥ 0.31
	## ## ## - ## + NaLS - ## ## ##	##	0.38	≥ 0.36
	SR ## ## - ## + ##### - ##### ## ##	##	0.29	≥ 0.19
	SR ## ## - ## + ##### - ## ## ##	##	0.27	≥ 0.22
	### ## #	###	188.6	0.1 - 1000
	ESD #	###	N/A	0.1 - 100
	#### ## ##	J	24	≥ 20
Top	##			
	#### ## # (## # ##### 100J)	mm	N/A	N/A
	#### ## # (## # ## ## 10kN)	mm	N/A	N/A
	#### ## # (## # ## ## 200J)	mm	17.0	≥ 14
	#### ## # (## # ## ## 15kN)	mm	22.5	≥ 14

##:
##, ## ## ##### ## # #####. ## ##### ## Safety Jogger # ##### ##, ### ## ## ## ## ##### ##### ## # #####.



Solutions for every workplace

INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP

ENGINEERED
IN EUROPE

www.safetyjogger.com