



SAFETY JOGGER

INDUSTRIAL



Medium

X200031 S3

##

X200031 ## #### SR ### ##, ## #### ##, S3 ### ## #### ##
####. ## #### #### #### ####.

## ##	#### ##
## ##	##
###	SJ # ##
##	##
###	BASF PU
Top	##
####	S3 / SR, SC, CI, FO
## ##	EU 36-48 / UK 3.5-13.0 / US 4.0-13.5 JPN 22.5-31.5 / KOR 235-315
## ##	0.654 kg
###	ASTM F2413:2018 EN ISO 20345:2022+A1:2024



LBR



S3

S3 #### ## ## ####
####. # ##

####.



SRC

####. SRC ### ##
SRA #
SRB ### ####.



###

####.



###

##.



##

##.

SAFETY
JOGGER
WORKS

Solutions for every workplace

INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP

ENGINEERED
IN EUROPE

www.safetyjogger.com

##:
###, ##, ##, ## # ##, ##

##:
##, ### ##

##:
#####. ### ##### ## ##### ## ##.

	##	## ##	##	EN ISO 20345
## ##	#### ##			
	##: ### ##	mg/cm²/h	4.07	≥ 0.8
	##: ### ##	mg/cm²	33	≥ 15
## ##	##			
	##: ### ##	mg/cm²/h	86.31	≥ 2
	##: ### ##	mg/cm²	691	≥ 20
###	SJ # ##			
	###: ####(##/##)(###)	##	25600/12800	25600/12800
###	BASF PU			
	### #####(## ##)	mm³	77	≤ 150
	## ## ## - ## + NaLS - ## ## ##	##	0.33	≥ 0.31
	## ## ## - ## + NaLS - ## ## ##	##	0.39	≥ 0.36
	SR ## ## - ## + ##### - ##### ## ##	##	0.24	≥ 0.19
	SR ## ## - ## + ##### - ## ## ##	##	0.24	≥ 0.22
	### ## #	###	58.0	0.1 - 1000
	ESD #	###	N/A	0.1 - 100
	#### ## ##	J	35	≥ 20
Top	##			
	#### ## #(## # ##### 100J)	mm	N/A	N/A
	#### ## #(## # ## ## 10kN)	mm	N/A	N/A
	#### ## #(## # ## ## 200J)	mm	16.0	≥ 14
	#### ## #(## # ## ## 15kN)	mm	24.0	≥ 14

##:
##, ## ## ##### ## # #####. ## ##### ## Safety Jogger # ##### ##, ### ## ## ## ## ##### ##### ## # #####.



Solutions for every workplace
INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP



www.safetyjogger.com