



**SAFETY
JOGGER**
INDUSTRIAL



Medium

X2020P31 S3

###

X2020P31 ## ##### ## ### ## ## ##, ### ## ## ## ## ##
#####. ### ## ## ## # ## ## ## ## ## ## ##.

## ##	#### ##
## ##	##
###	SJ # ##
##	##
###	BASF PU
Top	##
####	S3 / SR, SC, CI, FO
## ##	EU 36-48 / UK 3.5-13.0 / US 4.0-13.5 JPN 22.5-31.5 / KOR 235-315
## ##	0.631 kg
###	ASTM F2413:2018 EN ISO 20345:2022+A1:2024



##.



##.



##.



#####. 100##### 1### ##
##



S3
S3 ##### ## ## ## ## ##

#####.



LBR

**SAFETY
JOGGER**
WORKS

Solutions for every workplace

INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP

ENGINEERED
IN EUROPE

www.safetyjogger.com

##:
###, ##, ## # ##, ##

##:
##, ### ## ##, ##

##:
#####. ### ##### ## ##### ## ##.

	##	## ##	##	EN ISO 20345
## ##	#### ##			
	##: ### ##	mg/cm²/h	4.07	≥ 0.8
	##: ### ##	mg/cm²	33	≥ 15
## ##	##			
	##: ### ##	mg/cm²/h	86.31	≥ 2
	##: ### ##	mg/cm²	691	≥ 20
###	SJ # ##			
	###: #####(##/##)(###)	##	25600/12800	25600/12800
###	BASF PU			
	### #####(## ##)	mm³	77	≤ 150
	## ## ## - ## + NaLS - ## ## ##	##	0.33	≥ 0.31
	## ## ## - ## + NaLS - ## ## ##	##	0.39	≥ 0.36
	SR ## ## - ## + ##### - ##### ## ##	##	0.24	≥ 0.19
	SR ## ## - ## + ##### - ## ## ##	##	0.24	≥ 0.22
	### ## #	###	58.0	0.1 - 1000
	ESD #	###	N/A	0.1 - 100
	#### ## ##	J	35	≥ 20
Top	##			
	#### ## # (## # ##### 100J)	mm	N/A	N/A
	#### ## # (## # ## ## 10kN)	mm	N/A	N/A
	#### ## # (## # ## ## 200J)	mm	16.0	≥ 14
	#### ## # (## # ## ## 15kN)	mm	24.0	≥ 14

##:

#####. ## ##### ## Safety Jogger # ##### ##, ### ## ## ## ## ##### ##### ## # #####.



Solutions for every workplace

INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP

ENGINEERED
IN EUROPE

www.safetyjogger.com