



**SAFETY
JOGGER**
INDUSTRIAL



Heavy

X430 S7S

##

X430 ##### # ## ##### #####. ##, ### # #, #####
##, ### # # ## # ## #####.

##	##
##	###
###	SJ #
##	## #
###	PU/##
Top	##
####	S7S / SR, SC, ESD, ##, CI, FO, HRO
##	EU 36-50 / UK 3.5-14.0 / US 4.0-15.0
	JPN 22.5-33.0 / KOR 235-330
##	0.792 kg
###	EN ISO 20345:2022+A1:2024
	ASTM F2413:2024



#####.



DGUV BGR 191

#####. BGR 191# # #####.



300°C# ## # # ##.




ESD# ## ### ##### # # #

#####. # # 100#####
100### #####.



##(CI)
##(CI) ##### # # # # # # # #
#####.



#####. # # # # # # # # #
#.

**SAFETY
JOGGER**
WORKS

Solutions for every workplace

INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP

**ENGINEERED
IN EUROPE**

www.safetyjogger.com

##:
##, ###, ##, ##, ##, ###, ## # ##

##:
##, ### ##, ### ## ##, ### ##, ##

##:
#####. ### ##### ## ##### ## ##.

	##	## ##	##	EN ISO 20345
## ##	##			
	##: ### ##	mg/cm²/h	7.1	≥ 0.8
	##: ### ##	mg/cm²	64	≥ 15
## ##	####			
	##: ### ##	mg/cm²/h	2.4	≥ 2
	##: ### ##	mg/cm²	23	≥ 20
###	SJ # ##			
	###: #####(##/##)(###)	##	25600/12800	25600/12800
###	PU/##			
	### #####(## ##)	mm³	110	≤ 150
	## ## ## - ## + NaLS - ## ## ##	##	0.47	≥ 0.31
	## ## ## - ## + NaLS - ## ## ##	##	0.50	≥ 0.36
	SR ## ## - ## + ##### - ##### ## ##	##	0.20	≥ 0.19
	SR ## ## - ## + ##### - ## ## ##	##	0.26	≥ 0.22
	### ## #	###	3.6	0.1 - 1000
	ESD #	###	52	0.1 - 100
	#### ## ##	J	31	≥ 20
Top	##			
	#### ## #(## # ##### 100J)	mm	N/A	N/A
	#### ## #(## # ## ## 10kN)	mm	N/A	N/A
	#### ## #(## # ## ## 200J)	mm	18.0	≥ 14
	#### ## #(## # ## ## 15kN)	mm	21.0	≥ 14

##:
##, ## ## ##### ## # #####. ## ##### ## Safety Jogger # ##### ##, ### ## ## ## ## ##### ##### ## # #####.



Solutions for every workplace

INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP

ENGINEERED
IN EUROPE

www.safetyjogger.com