



**SAFETY
JOGGER**
INDUSTRIAL



Heavy

X430 EH SB

X430EH

EH ## ## ## ##

X430EH ## ## ## EH ## ##, SR ## ## ##, ## 300°C# ## ##
#####. ##, ##, ## ## ## ## ## ## ## ##.

## ##	##
## ##	####
###	SJ # ##
##	##
###	PU/##
Top	##
####	SB / PS, SR, SC, WR, E, ##, CI, FO, HRO
## ##	EU 36-48 / UK 3.5-13.0 / US 4.0-13.5 JPN 22.5-31.5 / KOR 235-315
## ##	0.790 kg
###	EN ISO 20345:2022+A1:2024 ASTM F2413:2024



##(EH)

##(EH)# ## ## ## ## ## ## ##
#####. 2# ## ## ## ## ## ## ##
#####.



##

#####.




##

300°C# ## ## ## ## ##.



##(CI)

##(CI) ##### ## ## ## ## ## ##
#####.



##

#####. ## ## ## ## ## ## ##
##.



SRC

#####. SRC ## ## ## ##
SRA #
SRB ## ## ## ## ## ## ##.

**SAFETY
JOGGER**
WORKS

Solutions for every workplace

INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP

**ENGINEERED
IN EUROPE**

www.safetyjogger.com

##:
###, ##, ##, ##, ##, ###, ## # ##

##:
##, ## ##, ### ##, ### ##

##:
#####. ### ##### ## ##### ## ##.

	##	## ##	##	EN ISO 20345
## ##	##			
	##: ### ##	mg/cm²/h	4.84	≥ 0.8
	##: ### ##	mg/cm²	45	≥ 15
## ##	####			
	##: ### ##	mg/cm²/h	2.6	≥ 2
	##: ### ##	mg/cm²	24.3	≥ 20
###	SJ # ##			
	###: ####(##/##)(###)	##	25600/12800	25600/12800
###	PU/##			
	### #####(## ##)	mm³	85	≤ 150
	## ## ## - ## + NaLS - ## ## ##	##	0.47	≥ 0.31
	## ## ## - ## + NaLS - ## ## ##	##	0.50	≥ 0.36
	SR ## ## - ## + ##### - ##### ## ##	##	0.20	≥ 0.19
	SR ## ## - ## + ##### - ## ## ##	##	0.26	≥ 0.22
	### ## #	###	N/A	0.1 - 1000
	ESD #	###	N/A	0.1 - 100
	#### ## ##	J	31	≥ 20
Top	##			
	#### ## #(## # ##### 100J)	mm	N/A	N/A
	#### ## #(## # ## ## 10kN)	mm	N/A	N/A
	#### ## #(## # ## ## 200J)	mm	19.0	≥ 14
	#### ## #(## # ## ## 15kN)	mm	22.5	≥ 14

##:
##, ## ## ##### ## # #####. ## ##### ## Safety Jogger # ##### ##, ### ## ## ## ## ##### ##### ## # #####.



Solutions for every workplace

INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP

ENGINEERED
IN EUROPE

www.safetyjogger.com