

```
## ##
##### ### ##### ##### ## #####
### ## ###.
```

##:
##, ###, ####, ## # ##, ##

##:
##

##:
#####. ### ##### ## ##### ## ##.

	##	## ##	##	EN ISO 20345
## ##	#####, ##			
	##: ### ##	mg/cm²/h	25.5	≥ 0.8
	##: ### ##	mg/cm²	204.4	≥ 15
## ##	###			
	##: ### ##	mg/cm²/h	25.5	≥ 2
	##: ### ##	mg/cm²	204.4	≥ 20
###	SJ # ##			
	###: ####(##/##)(###)	##	Dry 25600 cycles/Wet 12800 cycles	25600/12800
###	PU			
	### ####(## ##)	mm³	102.3	≤ 150
	## ## ## - ## + NaLS - ## ## ##	##	0.36	≥ 0.31
	## ## ## - ## + NaLS - ## ## ##	##	0.41	≥ 0.36
	SR ## ## - ## + #### - ##### ## ##	##	0.22	≥ 0.19
	SR ## ## - ## + #### - ## ## ##	##	0.23	≥ 0.22
	### ## #	###	357	0.1 - 1000
	ESD #	###	N/A	0.1 - 100
	#### ## ##	J	26	≥ 20
Top	##			
	#### ## # (## # ##### 100J)	mm	N/A	N/A
	#### ## # (## # ## ## 10kN)	mm	N/A	N/A
	#### ## # (## # ## ## 200J)	mm	17.0	≥ 14
	#### ## # (## # ## ## 15kN)	mm	22.5	≥ 14

##:

##, ## ## ##### ## # #####. ## ##### ## Safety Jogger # ##### ##, ### ## ## ## ## ##### ##### ## # #####.



Solutions for every workplace

INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP



www.safetyjogger.com